

## Tiras LED 14,4W IP20

### IP20 14,4W LED Strips

**GARANTÍA 3 AÑOS**  
**3 YEARS WARRANTY**



#### DESCRIPCIÓN · DESCRIPTION

Rollo de 5 metros de tira LED LightED tipo SMD a 24V con 14,4W/m y protección IP20 que alcanza los 1560lm/m. Se presenta en rollos de 5 metros pero puede cortarse cada 5cm. Posibilidad de suministro en rollos de 20 o 50 metros. Para tramos de tiras de LED de 10 metros de longitud y potencia 14,4W o superior, se recomienda alimentar por ambos extremos la tira LED. La conexión de 10 metros de tira LED continua alimentados desde un único extremo puede implicar una caída de tensión y luminosidad en el extremo opuesto de la alimentación

*Roll of 5 meters of LightED LED strip type SMD at 24V with 14.4W/m and IP20 protection that reaches 1560lm/m. It comes in rolls of 5 meters but it can be cut every 5cm. Possibility of supply in rolls of 20 or 50 meters. For sections of LED strips of 10 meters in length and power 14.4W or higher, it is recommended to feed the LED strip at both ends. The connection of 10 meters of continuous LED strip powered from a single end may imply a voltage and brightness drop at the opposite end of the supply*

#### ENLACES RELACIONADOS · RELATED LINKS

- [Declaración de conformidad CE · CE Declaration of conformity \(ES/EN\)](#)
- [ISO 9001](#)
- [ISO 14001](#)

#### GARANTÍA · WARRANTY

ALG le ofrece una garantía de **3 años** desde la fecha de compra.

*ALG offers you a 3-year warranty from the date of purchase.*



ALG dispone de un Sistema de Gestión de la Calidad según la norma ISO 9001 desde 1998 y desde el año 2021 estamos certificados con la norma 14001 para mejor conservación y protección del Medio Ambiente

*ALG has a Quality Management System according to the ISO 9001 standard since 1998 and since 2021 we have been certified with the 14001 standard for better conservation and protection of the Environment.*

## INFORMACIÓN TÉCNICA - TECHNICAL INFORMATION: WARM STRIPS (2200K/2700K/3000K)

## DATOS COMERCIALES / COMMERCIAL DATA

CODE	46251	46226	49170
REFERENCE	ROL2835 14,4W/M 24V 22K 5M IP20	ROL2835 14,4W/M 24V 27K 5M IP20	ROL2835 14,4W/M 24V 30K 5M IP20

## DATOS ELECTRICOS / ELECTRICAL DATA

INPUT VOLTAGE	24V	24V	24V
POWER	14,4W/M	14,4W/M	14,4W/M
POWER FACTOR	0,90	0,90	0,90

## DATOS FOTOMÉTRICOS / PHOTOMETRIC DATA

LUMINOUS FLUX (LM)	1560LM/M	1560LM/M	1560LM/M
CCT (KELVIN)	2200K	2700K	3000K
CRI	80	80	80
BEAM ANGLE	120°	120°	120°

## VIDA ÚTIL Y MEDIO AMBIENTE / LIFESPAN &amp; ENVIRONMENTAL DATA

ENERGY CLASS	E	E	E
LIFESPAN	25000h	25000h	25000h
WORKING TEMP.	-10°C~+40°C	-10°C~+40°C	-10°C~+40°C

## CARACTERÍSTICAS FÍSICAS / PHYSICAL CHARACTERISTICS

ROLL LENGTH	5M	5M	5M
WIDTH	8mm	8mm	8mm
IP PROTECTION	IP20	IP20	IP20
LED TYPE	2835	2835	2835
NUMBER OF LEDS/M	120	120	120
CUTTING	EVERY 5CM	EVERY 5CM	EVERY 5CM

## EMBALAJE / PACKAGING

CODE	46251	46226	49170
REFERENCE	ROL2835 14,4W/M 24V 22K 5M IP20	ROL2835 14,4W/M 24V 27K 5M IP20	ROL2835 14,4W/M 24V 30K 5M IP20
UNITS	1 ROLL (5 METERS)	1 ROLL (5 METERS)	1 ROLL (5 METERS)

INFORMACIÓN TÉCNICA - TECHNICAL INFORMATION: **WHITE STRIPS (4000K/6000K)****DATOS COMERCIALES / COMMERCIAL DATA**

CODE	49145	49146
REFERENCE	ROL2835 14,4W/M 24V 40K 5M IP20	ROL2835 14,4W/M 24V 60K 5M IP20

**DATOS ELECTRICOS / ELECTRICAL DATA**

INPUT VOLTAGE	24V	24V
POWER	14,4W/M	14,4W/M
POWER FACTOR	0,90	0,90

**DATOS FOTOMÉTRICOS / PHOTOMETRIC DATA**

LUMINOUS FLUX (LM)	1560LM/M	1560LM/M
CCT (KELVIN)	4000K	6000K
CRI	80	80
BEAM ANGLE	120°	120°

**VIDA ÚTIL Y MEDIO AMBIENTE / LIFESPAN & ENVIRONMENTAL DATA**

ENERGY CLASS	E	E
LIFESPAN	25000h	25000h
WORKING TEMP.	-10°C~+40°C	-10°C~+40°C

**CARACTERÍSTICAS FÍSICAS / PHYSICAL CHARACTERISTICS**

ROLL LENGTH	5M	5M
WIDTH	8mm	8mm
IP PROTECTION	IP20	IP20
LED TYPE	2835	2835
NUMBER OF LEDS/M	120	120
CUTTING	EVERY 5CM	EVERY 5CM

**EMBALAJE / PACKAGING**

CODE	49145	49146
REFERENCE	ROL2835 14,4W/M 24V 40K 5M IP20	ROL2835 14,4W/M 24V 60K 5M IP20
UNITS	1 ROLL (5 METERS)	1 ROLL (5 METERS)