

Panel LED Superficie 120CM 40-30-20W CCT

Surface LED Panel 120cm 40-20-30W CCT

GARANTÍA 5 AÑOS
5 YEARS WARRANTY

Con Selector de Potencia y CCT
With Power & CCT Selector



DESCRIPCIÓN - DESCRIPTION

Panel LED de superficie ideal para cocinas, de 120cm de largo y 10 de ancho, con tan solo 27mm de grosor. Incorpora un selector potencia con opción de 40W, 30W o 20W y otro de CCT para elegir la temperatura de color deseada. Regulable mediante TRIAC. Funciona directo a red, a 220-240V. Con un ángulo de apertura de 110° ofrece una iluminación uniforme en toda la estancia.

Surface LED panel ideal for kitchens, 120cm long and 10cm wide, only 27mm thick. It incorporates a power selector with the option of 40W, 30W or 20W and another CCT to choose the desired color temperature. Adjustable through TRIAC. It works directly from the network, at 220-240V. With an opening angle of 110°, it offers uniform lighting throughout the room.

GARANTÍA - WARRANTY

ALG le ofrece una garantía de **5 años** desde la fecha de compra.

ALG offers you a 5-year warranty from the date of purchase.



ALG dispone de un Sistema de Gestión de la Calidad según la norma ISO 9001 desde 1998 y desde el año 2021 estamos certificados con la norma 14001 para mejor conservación y protección del Medio Ambiente

ALG has a Quality Management System according to the ISO 9001 standard since 1998 and since 2021 we have been certified with the 14001 standard for better conservation and protection of the Environment.

INFORMACIÓN TÉCNICA - TECHNICAL INFORMATION

DATOS COMERCIALES / COMMERCIAL DATA

CODE	67837
REFERENCE	PANEL SUPERFICIE 10X120 40W/30W/20W CCT R

DATOS ELECTRICOS / ELECTRICAL DATA

INPUT VOLTAGE	220-240V
FREQUENCY	50Hz
POWER	40W / 30W / 20W
POWER FACTOR	0,90
DIMMABLE	TRIAC
IEC PROTECTION	Class I

DATOS FOTOMÉTRICOS / PHOTOMETRIC DATA

EFFICACY (LM/W)	95lm/W
LUMINOUS FLUX (LM)	3800lm / 2850 lm / 1900lm
CCT (KELVIN)	3000K / 4000K / 6000K
CRI	80
BEAM ANGLE	110°

VIDA ÚTIL Y MEDIO AMBIENTE / LIFESPAN & ENVIRONMENTAL DATA

ENERGY CLASS	E
CONSUMPTION	40kWh/1000h
LIFESPAN	50000h
WORKING TEMP.	-20°C~+40°C

CARACTERÍSTICAS FÍSICAS / PHYSICAL CHARACTERISTICS

SIZE	1213 x 100 x 27 mm
WEIGHT	2,020kg
IP PROTECTION	IP20
IK PROTECTION	IK05
BODY	ALUMINIUM

EMBALAJE / PACKAGING

CODE	67837
REFERENCE	PANEL SUPERFICIE 10X120 40W/30W/20W CCT R
UNITS	1
UNITS PER MASTER CARTON	6

DIMENSIONES - SIZE

